

Comsight Technology Co. Ltd.

Time and Temperature System Introduction

Comsight Technology CO., LTD.



Address : No.15 industrial 2nd street, Yaotiao industrial park, Torch High-tech Industrial Development Zone, Zhongshan city, Guangdong Province, PR China. Tel : 0086 0760 88789961~88789966(6 lines) Email : sales@comsight.cn Web : www.comsight.cn

Comsight Time and Temperature System

I. Features

- Can display: year, month, day, week, lunar calendar, Saudi calendar, time, Celsius temperature, Fahrenheit temperature, relative humidity, etc.;
- Can display temperature (default with meteorological temperature box)
- > 4-bit or 6-bit digital format: 88:88 or 88:88:88 or customized.
- > Adopt accurate clock chip DS3231SN to give high precision of time.
- > Multiple time calibration modes: GPS, NTP, IR remote control, 2-button RF remote control, communications, etc.
- > Alarm clock function: support up to 20 alarm clocks; default buzzer alarm sound; settable duration of time.
- > Time switch function: set the hour of turning ON/OFF display freely.
- High / low temperature alarm function: set the alarm temperature value freely; default buzzer alarm sound; settable duration of time.
- Alarm control signal output function: the output pin can be connected to an external relay for controlling other equipment.
- > Powerful and flexible configuration function: free to define a personalized Time & Temp. Display.
- > Power failure does not affect the accuracy of time and date.
- Customized design: different sizes and colors are available.

Some Extended Functions:

- Support extensions to display world time clock, support up to 20 time zones (need to connect more digits).
- Support connection of multiple temperature sensors. Can display multiple temperatures, such as water temperature (requires a special temperature sensor).
- Support alarm sounds from passive speakers, active speakers and music modules (requires an external speaker or voice module)
- > Support hourly tell time function. The validity of this function is settable (an external voice module is required).
- Support RGB color display (the digit should be RGB color)
- > Support simultaneous displaying for multiple TT displays (multiple TT displays are required networking).

Software function:

COMSIGHT

积目科技 consident TECHNOLOGY COMSIGHT	Comsight Technology CO., LTD. Address : No.15 industrial 2nd street, Yaotiao industrial park, Torch High-tech Industrial Development Zone, Zhongshan city, Guangdong Province, PR China.	Tel : 0086 0760 88789961~88789966(6 lines) Email : sales@comsight.cn Web : www.comsight.cn
	SMG_TimeTemperature(V2.8.4.1)	
	Time & Temperature	Settings for Communication
	Counter	
	Alarm Clock	
	Display Fixed Number	Close

- Setting pause time of each screen's content.
- Setting date format.
- Setting clock format.
- Setting daylight saving time. SD9901a
- > SD9902a
- > SD9903a
 - > Setting import and export method.
 - Adjust brightness.
 - Setting temperature offset value.
 - Select time zone.
 - Adjust time.
 - Setting World Clock.
 - Setting Counting up/Counting down, Enable/Disable counter.
 - Setting counter format.
 - Re-adjust sign's display.
 - > Setting temperature alarm mode.

Communication methods:

PC control: RS232/RS422/RS485(standard); LAN(TCP/IP), GSM, Bluetooth, 3G, GPRS

COMSIGHT



Comsight Technology CO., LTD.

Address : No.15 industrial 2nd street, Yaotiao industrial park, Torch High-tech Industrial Development Zone, Zhongshan city, Guangdong Province, PR China. Tel : 0086 0760 88789961~88789966(6 lines) Email : sales@comsight.cn Web : www.comsight.cn



RS232 Cable

COMSIGHT

RF remote control:



Typical Applications:

- > Transportation message: Airport, Train Station, Port, Express Way, Street
- > Public message: Hospital, School, Park, Market, Store, Hotel, Restaurant, Gas station, etc.
- Bulletin board: Factory, Bank, Post offices, Court, Customs, Government, etc.

